HM 2620 E



Meet the **HM 2620 E**. This professional hot air blower with digital display is used in a variety of sectors: plastic, construction, foil welding, shrinking of cable stockings, signalling foils, bumpers, etc. The temperature range (up to 700°C) makes it possible to weld plastics, do repairs, bend materials, make all kinds of connections, overlap plates, dry non-flammable paints and varnishes, defrost, etc.

HM 2620 E has these key advantages:

- Ergonomic handle (narrower than most models)
- Large power 2300W, which generates a large air flow rate
- Air filter in the wide part, so that the air does not have to pass through all the electronics.
- 4 Adjustable programs (temp. and flow rate)
- Visual indication when at the right temperature
- Automatic switch-off after cooling and residual heat indicator
- A transport case
- Very easy for maintenance:
    - Installing a new resistor is "plug and play".
    - Brushless motor
    - Separate section to change power cable, so that the whole device does not have to be opened.

TECHNICAL DATA

		HM 2620 E
Materials		TPO, PVC, PE, PP, PVDF, EPDM, Bitumen
Usable welding wire		see welding shoes
Power supply		230V
Output		2300 W
Hot Air Temperature		50-700 °C
Air supply		Includes
Air supply	l/min	150-500
Noise level	dBA	< 70 dB
Dimensions	L x W x H	358 x 91 x 95 mm
Weight	kg	1.16 kg

MACHINES

ST-110100381	HOT AIR BLOWER HM 2620 E – Digital – incl. transport case
ST-110100384	HOT AIR BLOWER HM 2620 E – Digital ROOFSET – incl. transport case, 2 nozzles, pressure roller

OPTIONS

Other	See options Hot air blowers

