

# HS ROLLERS



These "High Stand" **ROLLERS** are essential for supporting pipes while they are welded. The roller minimizes tube friction and tensile force, regardless of site conditions. They are user-friendly and light. Consequently, portable and easy to assemble and disassemble. The rollers were aligned at an angle so that the tube can be easily moved, even with welds on it.

## TECHNICAL DATA

|                |           | HS ROLLERS 250      | HS ROLLERS 355      | HS ROLLERS 630      | HS ROLLERS 1000     |
|----------------|-----------|---------------------|---------------------|---------------------|---------------------|
| Diameter range | ∅         | 75 - 250 mm         | 125 - 355 mm        | 225 - 630 mm        | 355 - 1000 mm       |
| Dimensions     | L x W x H | 1150 x 500 x 756 mm | 1421 x 600 x 818 mm | 1766 x 800 x 982 mm | 1788 x 900 x 859 mm |
| Weight         | Kg        | 26 kg               | 33 kg               | 55 kg               | 140 kg              |
| Max. tax       | Kg        | 500 kg              | 1000 kg             | 2000 kg             | 3000 kg             |

## ARTICLES

|          |                 |
|----------|-----------------|
| 87568600 | HS ROLLERS 250  |
| 87568601 | HS ROLLERS 355  |
| 87568602 | HS ROLLERS 630  |
| 98600303 | HS ROLLERS 1000 |