

RTC PIPE SCRAPER



RTC 160 & 315



RTC 500 & 710

These professional rotary scrapers are indispensable to prepare the plastic pipes (and fittings!) for electro welding. The scrapers remove the oxidation layer caused by the weather and UV rays. If this oxidation layer is not removed, this causes a poor quality of the connection.

This device makes it possible to keep the thickness of the pipe wall constant, even if it has a wrong shape. The length of the surface to be scraped can be adjusted. Both the RTC 500 and the 710 have an extendable arm for this, easy for work on site. The main clamp has four extendable arms that clamp to the inner wall of the tube.

TECHNICAL DATA

		RTC 160	RTC 315	RTC 500	RTC 710
Diameter range external	∅	50 - 160 mm	75 - 315 mm	180 – 500 mm	355 - 710 mm
Diameter range internal	∅	38 - 154 mm	58 - 300 mm	110 – 485 mm	290 - 675 mm
Max. scraping length	mm	114 mm	137 mm	500 mm	530 mm
Max. dimensions	L x B x H	380 x 120 x 250 mm	510 x 310 x 410 mm	780 x 250 x 500 mm	825 x 805 x 695 mm
Transport box size	L x B x H	390 x 210 x 135 mm	230 x 500 x 270 mm	750 x 480 x 280 mm	800 x 580 x 350 mm
Weight RTC	kg	2,5 kg	4,5 kg	14 kg	16 kg
Total weight	kg	5,65 kg	7,5 kg	24 kg	28 kg

ARTICLES

99850000	RTC 160 Pipe Scraper
99030000	RTC 315 Pipe Scraper
99050020	RTC 500 Pipe Scraper
99050010	RTC 710 Pipe Scraper

SPARE PARTS

76509030	Pipe Scraper Blade (round) RTC 500-710
76509020	Pipe Scraper Blade (round) RTC 160-315
65000050	Transport Case RTC 160
65000040	Transport Case RTC 315
65000190	Transport Case for- Scraper Arm
65000200	Transport Case for- Self Centering Head